delfin
INDUSTRIAL VACUUM SOLUTIONS

DM 40 WD - PROFESSIONAL WET & DRY

OEM ORIGINAL EQUIPMENT MANUFACTI

OEM ORIGINAL EQUIPMENT MANUFACTI

WINE









- ✓ Complete steel construction
- ✓ Three powerful by pass motors with independent cooling
- ✓ Compact and mobile
- ✓ Accessory kit included
- ✓ Improved hygiene and operational conditions
- ✓ Easy to handle
- ✓ Easy and safe to maintain
- ✓ Easy to clean and to maintain

SUCTION UNIT

Voltage	V - Hz	230 - 50 1 ~
Power	kW	3,45
Max water lift	mmH□O	2.500
Max air flow	m³/h	540
Suction inlet	mm	80
Noise level (EN ISO 3744)	dB(A)	76

FILTER UNIT

Filter Type		Bag
Surface - Diameter	cm²-mm	8.000 - 500
Material - Efficiency	IEC 60335-2-69	Polyester - L
Media - Filtration		Polypropilene - 100µm

COLLECTION UNIT

Discharge system		
Capacity	l	120

VOLUME

Dimensions	cm	68x63x105h
Weight	kg	50

COPYRIGHT © 2023 DELFIN S.R.L. ALL RIGHTS RESERVED
COPYRIGHT © 2023 DELFIN S.R.L. TUTTI I DIRITTI RISERVATI

www.delfinvacuums.com
delfin@delfinvacuums.it

SUCTION UNIT

The suction is provided by three by-pass motors, using carbon brushes, operated by independent switches and placed inside a sturdy steel casing, filled with soundproofing material.

FILTER UNIT

A floating device stops the suction whenever the liquid in the container reaches the maximum level and prevents overflowing.
The polyester bag filter, placed inside the filtering chamber, guarantees a wide filtering surface and high resistance to dust passage and clogging.

COLLECTION UNIT

The vacuum is assembled onto a sturdy steel chassis, and provided with industrial quality wheels , that make it suitable for mobile service even when used on rough surfaces.
Thanks to a discharge valve, it is possible to easily and safely empty the container.

OPTIONALS

- ✓ STAINLESS STEEL COLLECTION TANK

COPYRIGHT © 2023 DELFIN S.R.L. ALL RIGHTS RESERVED
COPYRIGHT © 2023 DELFIN S.R.L. TUTTI I DIRITTI RISERVATI