delfin
INDUSTRIAL VACUUM SOLUTIONS

MTL 202 DS LP - INDUSTRIAL SINGLE PHASE

BUILDING AND CONSTRUCTION

SURFACE PREPARATION









- ✓ Largest surface filter in its category
- ✓ Complete steel construction
- ✓ Two powerful by pass motors with independent cooling
- ✓ Compact and mobile
- ✓ Easy filter replacement
- ✓ Adjustable height to facilitate transport on vehicles
- ✓ Sliding dumper for DUSTOP system included
- ✓ Standard or Endless Bag interchangeable collection unit

SUCTION UNIT

Voltage	V - Hz	230 - 50
Power	kW	2,3
Max water lift	mmH□O	2.500
Max air flow	m³/h	360
Suction inlet	mm	50
Noise level (EN ISO 3744)	dB(A)	76

FILTER UNIT

Filter Type		Cartridge
Surface - Diameter	cm²-mm	30.000 - 360
Material - Efficiency	IEC 60335-2-69	Polyester - M PTFE
Air load on filter	m³/m²/h	120
Cleaning system		Dustop

COLLECTION UNIT

Discharge system		

VOLUME

Dimensions	cm	50x48x125h
Weight	kg	55

COPYRIGHT © 2023 DELFIN S.R.L. ALL RIGHTS RESERVED
COPYRIGHT © 2023 DELFIN S.R.L. TUTTI I DIRITTI RISERVATI

All data mentioned in this document may change without notice
Tutti i dati riportati in questo documento potrebbero variare senza avviso

www.delfinvacuums.com
delfin@delfinvacuums.it

delfin
INDUSTRIAL VACUUM SOLUTIONS

SUCTION UNIT

The suction is provided by two by-pass motors, using carbon brushes, operated by independent switches and placed inside a sturdy steel casing, filled with soundproofing material.

FILTER UNIT

The antistatic polyester cartridge filter placed inside the filter chamber guarantees a large filter surface and prevents the clogging of the filter.
It is possible to clean the filter using the Dustop, an integrated reverse pulse system: by closing the suction inlet and opening a flap in the filter chamber, the airflow generated by the motor cleans the filter thoroughly and safely, maintaining constant suction performance and preventing any dispersion of dust in the environment.

COLLECTION UNIT

The vacuumed material is discharged inside a 20 mt Endless Bag ; when the extremity of the bag is full, the operator can seal and dispose that part of the bag in total security, without coming in contact with dusts and spreading them in the environment

OPTIONALS

- ✓ OTHER VOLTAGES AND FREQUENCIES AVAILABLE UPON REQUEST
- ✓ ABSOLUTE HEPA FILTER /H14
- ✓ ANTISTATIC FILTER CLASS M
- ✓ STAINLESS STEEL CHASSIS
- ✓ REMOTE CONTROL
- ✓ STAINLESS STEEL CHAMBER

COPYRIGHT © 2023 DELFIN S.R.L. ALL RIGHTS RESERVED
COPYRIGHT © 2023 DELFIN S.R.L. TUTTI I DIRITTI RISERVATI