MTL 802 WXP - INDUSTRIAL SINGLE PHASE

OEM ORIGINAL EQUIPMENT MANUFACTI

BUILDING AND CONSTRUCTION

WINE

CLEANING CONTRACTORS

SURFACE PREPARATION









- ✓ Two powerful by pass motors with independent cooling
- ✓ Compact and mobile
- ✓ PPL filter for chips separation
- ✓ Discharge hose for liquids
- ✓ Accessory kit as standard
- ✓ Submerged pump for the discharge of the sucked liquid
- ✓ Stainless steel AISI304 collection tank
- ✓ Simultaneous operation of liquids vacuuming and discharge

SUCTION UNIT

Voltage	V - Hz	230 - 50
Power	kW	2,3
Max water lift	mmH□O	2.500
Max air flow	m³/h	360
Suction inlet	mm	50
Noise level (EN ISO 3744)	dB(A)	76

FILTER UNIT

Media - Filtration		Polypropilene - 300µm

COLLECTION UNIT

Discharge system		
Capacity	l	80
Discharge speed	l / min	100

VOLUME

Dimensions	cm	53x59x105h
Weight	kg	50

COPYRIGHT © 2023 DELFIN S.R.L. ALL RIGHTS RESERVED
COPYRIGHT © 2023 DELFIN S.R.L. TUTTI I DIRITTI RISERVATI

delfin
INDUSTRIAL VACUUM SOLUTIONS

SUCTION UNIT

The suction is provided by two by-pass motors, using carbon brushes, operated by independent switches and placed inside a sturdy steel casing, filled with soundproofing material.

FILTER UNIT

A floating device stops the suction whenever the liquid in the container reaches the maximum level and prevents overflowing.

COLLECTION UNIT

The vacuum cleaner is mounted on a solid steel trolley, provided with a support for hoses when not used, and equipped with oil proof wheels and braking castors.
The stainless steel collection tank has a quick system for the rapid disposal of the sucked material.
The filtered liquid can be discharged easily and quickly thanks to a submersible pump

OPTIONALS

✓ OTHER VOLTAGES AND FREQUENCIES AVAILABLE UPON REQUEST

COPYRIGHT © 2023 DELFIN S.R.L. ALL RIGHTS RESERVED
COPYRIGHT © 2023 DELFIN S.R.L. TUTTI I DIRITTI RISERVATI